

# TOPRING QUICK COUPLERS AT A GLANCE

For a 1/4 INDUSTRIAL type quick coupler, many options are available. It is important to consider these criteria:

- 1) Required profile (ex: 1/4 INDUSTRIAL)
- 2) Air flow (**SCFM**) required by the air tool
- 3) Air pressure (**PSI**) required by the air tool
- 4) Is safety important in your work environment? (safety coupler)
- 5) Is the tool disconnected frequently? (manual or automatic connection)
- 6) Other specific requirements? (ex : lightweight, compact, anti-scratch, **UNIVERSAL**)



TOPRING

.com



1/4 INDUSTRIAL										
Brand	MAXQUIK	AUTOMAX	AUTOMAX SLIM	MAXQUIK PLUS	UNIQUIK	UNISAFE	UNIMAX	UNIQUIK SLIM	QUIKSILVER	TOPQUIK
Product No	20.842 (F) 20.942 (M)	20.444 (F) 20.644 (M)	20.443 (F) 20.643 (M)	20.844 (F) 20.944 (M)	20.440 (F) 20.640 (M)	20.448 (F) 20.648 (M)	20.441 (F) 20.641 (M)	20.433 (F) 20.633 (M)	20.446 (F) 20.646 (M)	20.449 (F) 20.649 (M)
SCFM (Air flow)	24	37	45	37	35	34	37	44	44	36
PSI (Pressure)	250	250	150	250	150	200	200	150	500	225
Connection	Manual	Automatic	Automatic	Manual	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Safe	-	-	-	-	-	●	-	-	-	●
Other features	-	-	Compact Lightweight	Available in stainless steel	<b>UNIVERSAL</b> accept 3 type of plugs	<b>UNIVERSAL</b> accept 5 type of plugs	<b>UNIVERSAL</b> accept 5 type of plugs	Compact Lightweight <b>UNIVERSAL</b> accept 3 type of plugs	Drag guard protects against accidental disconnection	Lightweight Anti-scratch